



# Brava™

PVC-FREE WALL COVERING

## Satin 180

Technical Data Sheet

### Product Details:

High quality coated smooth nonwoven for digital printing.

### Surface Aspect:

- Semi Glossy

### Printing Process:

- Latex / UV

### Printer Benefits:

- High dimensional stability
- Good opacity
- Excellent printability

### End User Benefits:

- PVC-free and ECO-friendly
- Luxurious, textile-like touch
- 100% paste-the-wall and strippable

### Certification

ASTM E-84 Class A

Certified for  
HP Latex Inks



The mark of  
responsible forestry

(On Request)

### Physical Properties

Grammage	180 g/m <sup>2</sup>	5.30 oz/yd <sup>2</sup>
Thickness	235 µm	9.25 mils
Dry Tensile Strength MD	8950 N/m	23,175 g/inch
Dry Tensile Strength CD	5450 N/m	14,100 g/inch
Elongation MD	5	%
Elongation CD	11.5	%
Ratio Wet/Dry	40	%
Brightness	87	%
Opacity	94	%
Wet Stability CD (Maxi)	0.25	%
Side to be printed	Top coated	

### Disclaimer:

This information is provided for reference purposes only and should not be constructed as a specification or warranty of performance.

**ecologicalfibers,inc.**

ENVIRONMENTALLY SOUND COVER SOLUTIONS

40 PIONEER DRIVE, LUNUNBURG,

MA 01462 USA

TEL: (978) 537 - 0003

INFO@ECOFIBERS.COM