



PRODUCT DETAILS

	SURFACE				PRINTING PROCESS							CERTIFICATIONS			
	SEMI GLOSS	MATTE	FIBROUS	SMOOTH	LATEX INK JET	UV INK JET	LASER JET	GRAVURE	FLEXOGRAPHY	WATER BASED INK JET	FSC CERTIFIED	W102	HP LATEX INK	XEIKON	ASTM E-84 CLASS A
TYPE II			X	X	X		X	X		X	X	X			X
FIBROUS			X	X	X	X			X	X	X	X	X		X
MATTE		X		X	X	X			X	X	X	X			X
SATIN	X			X	X	X				X	X	X			X

PHYSICAL PROPERTIES

	GRAMMAGE	THICKNESS	DRY TENSILE STRENGTH MD	DRY TENSILE STRENGTH CD	ELONGATION MD	ELONGATION CD	BRIGHTNESS	OPACITY	WET STABILITY CD
TYPE II	300 g/m ²	500.38 µm	8825 N/m	6175 N/m	8.1%	16.1%	85%	95%	< 0.1%
FIBROUS	147 g/m ²	380 µm	3400 N/m	2200 N/m	7%	10%	91%	93%	0.20%
MATTE	147 g/m ²	260 µm	4850 N/m	3000 N/m	5%	12.5%	87.5%	92%	0.25%
SATIN	180 g/m ²	235 µm	8950 N/m	5450 N/m	5%	11.5%	87%	94%	0.25%

AVAILABILITY

	CARTON PACKED	SKID PACKED	LARGE ROLL
TYPE II	50 yd x 54 in	50 yd x 54 in	200-1000 yd x 54 in
FIBROUS	50 yd x 30 in 50 yd x 60 in	50 yd x 30 in 50 yd x 60 in	200-1000 yd x 30 in 200-1000 yd x 60 in
MATTE	50 yd x 54 in	50 yd x 54 in	200-1000 yd x 54 in
SATIN	50 yd x 54 in 50 yd x 60 in	50 yd x 54 in 50 yd x 60 in	200-1000 yd x 54 in 200-1000 yd x 60 in

CUSTOM ROLL SLITTING

is available for a surcharge. Consult with a sales representative to learn more!

