



Brava™

PVC-FREE WALL COVERING

Satin

Technical Data Sheet

Product Details:

High quality coated smooth nonwoven for digital printing. This material is PFAS free, formaldehyde free, and heavy metal free.

Surface Aspect:

- Semi Glossy

Printing Process:

- Latex / UV

Printer Benefits:

- High dimensional stability
- Good opacity
- Excellent printability

End User Benefits:

- PVC-free and ECO-friendly
- Luxurious, textile-like touch
- 100% paste-the-wall and strippable

Certification

ASTM E-84 Class A

Certified for
HP Latex Inks



The mark of
responsible forestry

(On Request)

Physical Properties

Grammage	180 g/m ²	5.30 oz/yd ²
Thickness	235 µm	9.25 mils
Dry Tensile Strength MD	8950 N/m	23,175 g/inch
Dry Tensile Strength CD	5450 N/m	14,100 g/inch
Elongation MD	5	%
Elongation CD	11.5	%
Ratio Wet/Dry	40	%
Brightness	87	%
Opacity	94	%
Wet Stability CD (Maxi)	0.25	%
Side to be printed	Top coated	

Sustainability



Disclaimer:

This information is provided for reference purposes only and should not be constructed as a specification or warranty of performance.

ecologicalfibers, inc.

ENVIRONMENTALLY SOUND COVER SOLUTIONS

40 PIONEER DRIVE, LUNenburg,
MA 01462 USA

TEL: (978) 537 - 0003

INFO@ECOFIBERS.COM