



Brava™

PVC-FREE WALL COVERING

Type II

Technical Data Sheet

Product Details:

High quality uncoated nonwoven for digital printing. This FSC® certified material is PFAS free, formaldehyde free, and heavy metal free.

Meets all Type II requirements.

Surface Aspect:

- Smooth

Printer Benefits:

- PVC-free
- High tear (Type II US)
- Excellent printability

Printing Process:

- Gravure / flexography / digital
- UV / Latex

End User Benefits:

- PVC-free and ECO-friendly
- Luxurious, textile-like touch
- 100% paste-the-wall and strippable

Certification



The mark of responsible forestry

(On Request)

Physical Properties

Grammage	300 g/m ²	13.2 oz/yd ²
Thickness	500.38 µm	19.7 mils
Grab Tensile Strength MD	59,140	grams
Grab Tensile Strength CD	47,925	grams
Elongation MD	8.1	%
Elongation CD	16.1	%
Brightness	85	%
Opacity	95	%
Wet Stability (Max)	< 0.1	%
Side to be printed	Top	

* Embossing this material will not affect any physical properties or certifications listed.

Sustainability



Disclaimer:

This information is provided for reference purposes only and should not be constructed as a specification or warranty of performance.

ecologicalfibers, inc.

ENVIRONMENTALLY SOUND COVER SOLUTIONS

40 PIONEER DRIVE, LUNenburg,
MA 01462 USA

TEL: (978) 537 - 0003
INFO@ECOFIBERS.COM